Sliding 90 cm Chimney Hood

DKB4950M



Clean lines, clean air
Powered by an energy-efficient motor, this well-designed chimney hood is installed against the wall, effectively reduces kitchen odours while adding to the look and feel of the space itself.

Powered by an energy-efficient motor, this well-designed chimney hood is installed against the wall, effectively reduces kitchen odours while adding to the look and feel of the space itself.

Product Benefits & Features

Clean air. Designed to last
This filter captures and cleans away cooking smells incredibly efficiently to leave kitchens fresh. The longest-lasting disposable filter, it can be washed and reactivated to ensure it maintains its high odour-filtering performance.

- Electronic variable 3 speed push button control
- Washable aluminium grease filters
- Extraction mode
- Recirculation or extraction options
- For wall mounting between furniture or as a stand alone unit



Benefit from long-lasting lighting
Gain the benefits of LED lighting. Clear and bright, it makes ideal task lighting over a hob and, additionally, it's long-lasting and energy-efficient too.

Hood settings. On demand
Innovative electronic controls make regulating the cooker hood functions more convenient. From modifying the fan speed to adjusting the light settings, take complete control of the cooking process.

AEG

Sliding 90 cm Chimney Hood

DKB4950M

Product Specification

Installation	Chimney
Size	90
Dimensions, HxWxD	665-1090x898x500
Minimum distance from cooking top	50
Minimum distance from cooking top	65
Cord Length	1.5
Voltage	220-240
Frequency	50
Colour	Stainless steel
Charcoal filter type	MCFE01
Other comments technical specifications	IN RECIRCULATION: Height min.-max. external, mm 720-1070mm
Superperforming charcoal filter compatible	SUPCHARC-E, 942 150 224
Energy class	B
Fluid dynamic efficiency class	B
Lighting efficiency class	A
Grease filter efficiency class	C
Capacity minimum, m3/h	240
Capacity, Max m³/h	603
Sound power min speed, dB(A)	46
Sound power max speed, dB(A)	69
No. of speed settings	3
Lamp type	LED spotlight
No. of lamps	2
Grease filters	2
Chimney denomination	n/a
Recirc sound power min, dB(A)	66
Recirc sound power max, dB(A)	75
Recirculation min, m3/h	224
Recirculation max, m3/h	400
ProdPartCode	B - Open All