product information sheet

Trade Mark	AEG
Model	DPB3631S 942022050
Annual Energy Consumption (kWh/year)	54.3
Energy Efficiency class	C
Fluid Dynamic Efficiency	13.4
Fluid Dynamic Efficiency class	D
Lighting Efficiency (lux/W)	12
Lighting Efficiency class	E
Grease Filtering Efficiency	65.1
Grease Filtering Efficiency class	D
Air flow at minimum and maximum speed in normal use (m3/h)	155/370
Air flow at intensive or boost setting (m3/h)	-
Airborne acoustical A-weighted sound power emissions at minimum and maximum speed in normal use (dB(A))	48/68
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	-
Power consumption in off mode (W)	0
Power consumption in standby (W)	0.01

Attribute Name	Symbol	Value	Unit
Model Denomination		DPB3631S 942022050	
Annual Energy Consumption	AEC_{hood}	54.3	kwh/a
Time increase factor	f	1.5	
Fluid Dynamic Efficiency	FDE_{hood}	13.4	
Energy Efficiency Index	EEI_{hood}	79.4	
Measured air flow rate at best efficiency point	Q_{BEP}	216.3	m3/h
Measured air pressure at best efficiency point	P_{BEP}	198	Pa
Maximum air flow	Q_{max}	370,0	m3/h
Measured electric power input at best efficiency point	W_{BEP}	88.5	W
Nominal power of the lighting system	W_L	8,0	W
Average illumination of the lighting system on the cooking surface	E_{middle}	96	lux
Measured power consumption in standby mode	P_S	0	W
Measured power consumption off mode	P_O	0.01	W
Sound power level	L_{WA}	68	dB

EN 60704-2-13 - Household and similar electrical appliances – Test code for the determination of airborne acoustical noise – Part 2-13: Particular requirements for range hoods

EN 50564 - Electrical and electronic household and office equipment. Measurement of low power consumption

Suggestions for a correct use in order to reduce the environmental impact:
• Switch ON the hood at minimum speed when you start cooking and kept it running for few minutes after cooking is fi nished.
• Increase the speed only in case of large amount of smoke and vapour and use boost speed(s) only in extreme situations.
• Replace the charcoal filter(s) when necessary to maintain a good odour reduction effi ciency.
• Clean the grease filter(s) when necessary to maintain a good grease fi lter effi ciency.
• Use the maximum diameter of the ducting system indicated in this manual to optimize effi ciency and minimize noise.