CAT. N° 0 326 86



PATCH CORD FIBRE OPTIC LCS³ - OS1/OS2 SINGLE-MODE - LC/LC UNIBOOT DUPLEX - REVERSIBLE POLARITY - 1 M

Pack (number of units)	3
Volume (dm³)	2,948
Weight (g)	120,00

Product characteristics

OS1/OS2 single-mode fibre optic cords (9/125 µm)

- Max. optical losses/Master: 0.25 dB
- For 9/125 µm single-mode installations, OS 1/OS 2 type
- Yellow sheaths

LC/LC Uniboot duplex cords

- Reversible polarity
- Length: 1 m

General characteristics

Legrand cabling system, fibre optic LCS³ - patch cords and feedthrough sockets

- Fitted at each end with 2 connectors with ceramic ferrule. Individually packed and tested (report supplied)
- LSZH Zipcord sheath
- Other configurations on request

Documentation

Catalogue pages & additional information

- Selection chart (p.719)
- Description page (p.751)

Installation & technical data

- S000100292EN-02

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.