## CAT. N° 0 326 88



# PATCH CORD FIBRE OPTIC LCS³ - OS1/OS2 SINGLE-MODE - LC/LC UNIBOOT DUPLEX - REVERSIBLE POLARITY - 3 M

| | |
|---|---|
| Pack (number of units) | 3 |
| Volume (dm³) | 2,948 |
| Weight (g) | 159,00 |

## Product characteristics

**OS1/OS2 single-mode fibre optic cords (9/125 µm)**
- Max. optical losses/Master: 0.25 dB
- For 9/125 µm single-mode installations, OS 1/OS 2 type
- Yellow sheaths

**LC/LC Uniboot duplex cords**
- Reversible polarity
- Length: 3 m

## General characteristics

**Legrand cabling system, fibre optic LCS³ - patch cords and feedthrough sockets**
- Fitted at each end with 2 connectors with ceramic ferrule. Individually packed and tested (report supplied)
- LSZH Zipcord sheath
- Other configurations on request

## Documentation

**Catalogue pages & additional information**
- Selection chart (p.719)
- Description page (p.751)

**Installation & technical data**
- S000100292EN-02

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.