CAT. N° 0 784 57



LIGHTING MANAGEMENT-TRAFFIC DETECTION-FLUSH MOUNTING- IR - 180°- RANGE 8 M

Pack (number of units)	1
Volume (dm³)	0,235
Weight (g)	60,00

Product characteristics

2-wire motion sensor for time-lag switch, without neutral

- To be associated with a time-lag switch
- Allows automatic turning on/off in a hall, staircase...
- Replaces a push-button
- The time delay setting must be the same as that of the time-lag switch
- Cardboard
- Range 8 m
- White - without neutral
- To be associated with a modular time-lag switch
- Replaces a push-button
- Recommended fixing height: 1.2 m
- Standby consumption: 0.2 W
- Adjustable time-delay: 30 s. to 12 min
- The time delay must be the same for the sensors and the time lag switch

General characteristics

Mosaic™ Programme mechanisms - motion and presence sensors

- All sensors are compatible with any lamp - Detection field: 120°
- Detection range: 8 m
- Recommended installation height: 1.20 m
- Integrated self-protection against overloads and short-circuits.
- 2 modules

Documentation

Catalogue pages & additional information

- Selection chart (p.658)
- Selection chart (p.659)
- Description page (p.661)
- Technical page (p.662)
- Description page (p.880)
- Motion sensors and Lighting Management sensors for controllers

Agreements & certificates of conformity

- OC / CB - 645761D

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.