CAT. N° 0 784 58



180° MOTION SENSOR -IP40 -8 M -FLUSH-MOUNTING -WITHOUT OVERRIDE -PIR -CARDBOARD

Pack (number of units)	1
Volume (dm³)	0,235
Weight (g)	93,00

Product characteristics

2-wire motion sensors, without neutral

- IR detection
- Accepted power by lamp type:
  - LEDs: 3 to 100 W
  - compact fluorescent: 3 to 100 W
  - LEDs, CFLs, Halogen, fluo tubes with ferromagnetic or electronic transformer: 3 to 250 VA
  - halogen 230 V, incandescent: 3 to 250 W
- For LED and compact fluorescent lamps
- If several sensors are installed on the same circuit, the minimum load changes: refer to the technical sheet
- Possibility to install up to 3 sensors in parallel
- Time delay setting from 10 s to 10 min
- Light level threshold setting from 5 lux to 1275 lux
- Standby consumption : 0.2 W

Sensor without override

- Cardboard
- Range 8 m
- Recommanded fixing height: 1.2 m
- 2-wire without neutral
- Light level threshold: 5 to 1275 lux
- Adjustable time delay: 10 s to 10 min
- Standby consumption: 0.2 W

General characteristics

Mosaic™ Programme mechanisms - motion and presence sensors

- All sensors are compatible with any lamp - Detection field: 120°
- Detection range: 8 m
- Recommended installation height: 1.20 m
- Integrated self-protection against overloads and short-circuits.
- 2 modules

Documentation

Catalogue pages & additional information

- Selection chart (p.658)
- Selection chart (p.659)
- Description page (p.661)
- Technical page (p.662)
- Description page (p.880)
- Technical page (p.882)
- Motion sensors and Lighting Management sensors for controllers

Installation & technical data

- F01983EN-03

Installation instructions & related documents

- LE08095AD

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.