

MS3-2D

Barcode Scanner 2D, with Stand

Model	MS3-2D		
	Barcode Scanner, 2D, with stand		
Interface	USB	Sensor	Planar CMOS sensor
Light source	Red CCD, white LED (lighting)	Procesor	32-bit ARM MCU
Decoding capability	1D: Codabar, Code39, Code32, InterLeaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code93, Code128, Cs1-28, UPC-A, UPC-E, EAN/JAN-8, EAN-JAN-13, ISSN, GS1 DATABAR (RSS14), GS1 DATABAR Limited, GS1DATABAR Expanded 2d: PDF417, QR CODE, MICRO QR, DATAMATRIX, AZTEC CODE	Resolution	Code39 3mil, QR 8,7mil, PDF417 5mil, PCS45%
Scanning speed	200scans/sec	Scanning method	Manual&Auto-sensing
Scanning area	5*5cm² - 30*30cm²	Prompting mode	Buzzer, indicator light (LED)
Printing contrast	No lower than 35%	Scanning angle	Roll 0-360°, pitch ±65°, yaw±60°
IP Grade	IP54	Power supply	DC 5V
Operating temperature	0 to 50°C/32 to 122°F	Storage temperature	0 to 50°C/32 to 122°F
Operating humidity	5-95% (non-condensing)	EDS protection	15KV air discharge
Shock resistance	1.5 free all on concrete surface	Size	170mmx97mmx68mm
Warranty	2 years		