WHI949EXBG

Freestanding wall decorative cooker hood



Polyurethane filter

Re-circulating hoods

Noise level

Useful tips

What capacity do you need?

Wall mounted cooker hood
Venting with air extraction or recirculation
Energy class: **B**
Material of housing/chimney: **Painted steel/glass / stainless steel**
Colour of housing/chimney: **silver / stainless steel**

Lightning efficiency class: **A**
Grease filtering efficiency class: **C**
Fluid dynamic efficiency class: **B**
Maximum extraction rate by extraction operation: **608 m³/h**
Maximum extraction rate by recirculation operation: **374 m³/h**
Venting tube diameter: **15 cm**

Air flow by extraction version, step 1: **367 m³/h**
Air flow by extraction version, step 2: **447 m³/h**
Air flow by extraction version, step 3: **608 m³/h**

Electronic control
Number of speed positions: **3**

Lamp type: **Led strip**
On/off light switch
Number of lights: **1**
Power of lights: **3 W**

Filter material: **Washable aluminium with polyurethane foam**
Coal filter code (optional as separate purchase): **808996**
Recirculation set number: **735631**
Number of motors: **1**
No return airflow flap: **150 mm**

Max. noise level: **63 dB(A)re 1 pW**
Height: **380 mm**
Min. height of the chimney: **575 mm**
Max. height of the chimney: **705 mm**
Annual energy consumption: **59.2 kWh**
Dimensions (W×H×D): **90 × 38 × 33.5 cm**
Dimensions of packed product (W×H×D): **99 × 54.5 × 40 cm**
Net weight: **14.6 kg**
Gross weight: **19.12 kg**
Consumption in standby mode: **0.63 W**
Connected load: **183 W**
Nominal current of fuse: **10 amp**
Product code: **735479**
EAN code: **3838782389825**

https://th.gorenje.com/en/product/735479