

PowerShield 27W DC UPS, 13V Out, Floating, 3-Conductor NAM Pwr Cord

CP27U13NA3-S

Call for More Information

- Includes: User manual

Output

Output power capacity	27 Watts / 27VA
Max Configurable Power (Watts)	27 Watts / 27VA
Output Voltages	12
Output Connections	(2) Screw terminals (2) Screw Terminals

Input

Input frequency	47 - 70 Hz Auto-sensing
Input Connections	IEC 60320 C5
Cord Length	2.4meters
Input voltage range for main operations	87 - 264V
Input Voltages	100 - 240
Number of Power Cords	1

Communications & Management

Control panel	LED Status display with on line : on battery, Output power on indicator LED
Audible Alarm	Alarm when on battery : distinctive low battery alarm

Physical

Maximum Height	190MM, 19.0CM
Maximum Width	241MM, 24.1CM
Maximum Depth	76MM, 7.6CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Physical

Net Weight	3.41KG
Shipping weight	4.09KG
Shipping Height	343MM, 34.3CM
Shipping Width	343MM, 34.3CM
Shipping Depth	114MM, 11.4CM
Color	Beige
Units per Pallet	90.0

Environmental

Operating Temperature	-20 - 50 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

Conformance

Approvals	C-Tick, CE, cUL listed, EN 55022 class B, EN 60950, EN 61000-3-2, FCC part 15 class B, IEC 60950, UL 60950, UL listed
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.