PHILIPS

Lighting



Ledinaire Waterproof Tube Housing

WT050C 2xTLED L1200

220 to 240 V - 50 or 60 Hz - Safety class II - Dust penetration-protected, jet-proof - 5 J vandal-protected - White

The Ledinaire range contains a selection of popular off-the-shelf LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable – just what you need.

Product data

General information	
Luminaire light beam spread	-
Protection class IEC	Safety class II
CE mark	CE mark
Material	Polycarbonate
Angle	-
Accessory color	White

Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz

Mechanical and housing	
Overall length	1275 mm
Overall width	95 mm
Overall height	84 mm
Dimensions (Height x Width x Depth)	84 x 95 x 1275 mm (3.3 x 3.7 x 50.2 in)

Approval and application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]

Initial performance (IEC compliant)	
Init. Color Rendering Index	-
Initial input power	- W


Product data	
Full product code	871016336603699
Order product name	WT050C 2xTLED L1200
EAN/UPC - Product	8710163366036
Order code	911401807481
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	9
Material Nr. (12NC)	911401807481
Net Weight (Piece)	0.950 kg

Ledinaire Waterproof Tube Housing

IP65 IK08

Dimensional drawing

WT050C L1200 2 Tube



WT050C 2xTLED L1200

© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.