FM09IDU32

12NC: 859991584190

GTIN (EAN) code: 8003437602917

SENSING THE DIFFERENCE



Whirlpool air conditioner - FM09IDU32

This Whirlpool freestanding air-conditioner features: white color. Jet function, thanks to this innovative function it is possible to reduce the temperature by 5C in just 10 minutes. Inverter heat pump. "AROUND U" function, the sensor in the remote control measures the room temperature in the place where you are and sends the information to the internal unit that adjust its cooling on the basis of this information ensuring the optimal temperature in all the room. Delayed start, plan when turn on your air conditioner.

- Type: Split
- Inverter air conditioning
- BTU cooling capacity: 9000
- Main colour of product: White
- Sleep mode
- Jet function
- 4D air flow
- Around U function
- Dehumidification function
- Power save mode
- Filter type: HEPA + Catechin
- Type of User Interface: LED
- Temperature display (°C): Yes
- Remote control: Yes
- Sound pressure noise level Indoor unit - Silent mode
- Container Loading Capacity (20'/40'/40'HQ): 362/740/846
- Gross weight (kg): 10.5
- Net weight (kg): 8.5
- Dimensions Indoor unit HxWxD: 270x905x210 mm
- Reversible Flow
- Depth packed Indoor unit: 335
- Gross weight Indoor unit: 11
- Net weight Indoor unit: 8.5

Reversible
REVERSIBLE AIR CONDITIONER, the smart option for winter. Enjoy cool air during hot summer as well as warm temperature in winter thanks to the heating function of your air conditioner.

6TH SENSE Technology
6th SENSE TECHNOLOGY Thanks to the temperature sensor, the unique 6th sense technology can automatically select the oprating mode that is more suitable for you.

Silent mode
SILENT MODE This option allows the product to operate at low noise level to get a quiet and comfortable room environment.

9000 BTU
9000 BTU cooling capacity, recommended for rooms of 14.5 - 17 m2.

Remote Control
REMOTE CONTROL Easy to use remote control to activate all functions and get the best from your air conditioner.

HEPA Air Filter
HEPA filter can remove up to 99.9% of particles greater than 0.3 µm, which is the size of most allergen particles.

New Night Mode
4 AGES SLEEP MODE, the best sleep experience is guaranteed Thanks to the 4 dedicated temperature and humidity sleep profile, you'll find the one which is fitting to your age for your maximum comfort during night.

4D Xpert
4D XPERT AIRFLOW: Thanks to side air vents, the special configuration of the indoor unit can provide more uniform air circulation.

Around U
AROUND U FUNCTION Thanks to a temperature sensor inside the remote control, your ideal temperature will be set around you, to make you feel more comfortable.

FM09IDU32

12NC: 859991584190

GTIN (EAN) code: 8003437602917

Whirlpool
SENSING THE DIFFERENCE

DIMENSIONS

Current (A)	0,2
Frequency (Hz)	50
Depth IDU	210
Depth ODU	0
Depth packed IDU	335
Depth packed ODU	0
Gross weight IDU	11
Gross weight ODU	0
Height IDU	270
Height ODU	0
Height packed IDU	265
Height packed ODU	0
Net weight IDU	8.5
Net weight ODU	0
Width IDU	905
Width ODU	0
Width packed IDU	940
Width packed ODU	0

TECHNICAL FEATURES

Auto defrost	No
Dehumidification function	Yes
Room temperature display	No
Refrigerant gas type	N/A

PERFORMANCES

Energy class cooling	N/A
Energy class heating	N/A
Air Volume ODU - rated fan speed	0
Annual energy consumption during cooling season - kWh/annum	0
Annual energy consumption during heating season average (Green) - kWh/annum	0
Capacity Range Cooling Max	0
Capacity Range Cooling Min	0
Capacity Range Heating Max	0
Capacity Range Heating Min	0
Cooling sound power value for IDU	0
Cooling sound power value for ODU	0
COP Heating	0
Declared capacity (kW)	0
EER Cooling	0
Heating sound power value for IDU	0
Heating sound power value for ODU	0
Rated capacity heating (kW)	0
SCOP heating average (Green)	0
SEER cooling	0
Sound pressure noise level IDU - Silent mode	19
Sound pressure noise level ODU	0
Working T° Range Cooling - Indoor range	21°C - 32°C
Working T° Range Cooling - Outdoor range	N/A
Working T° Range Heating - Indoor range	20°C - 27°C
Working T° Range Heating - Outdoor range	N/A
Max current Cooling	0.3
Max current Heating	0.3