

Ledinaire Waterproof

WT060C LED25S/840 PSU TW1 L1200

840 neutral white - Power supply unit

The Ledinaire range contains a selection of popular off-the-shelf LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable – just what you need.

Product data

General information	
Beam angle of light source	120 °
Light source color	840 neutral white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Symmetrical
Luminaire light beam spread	120°
Control interface	-
Connection	Connection unit 3-pole
Cable	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 850 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	10

EU RoHS compliant	Yes
Service tag	No
Unified glare rating CEN	Not applicable

Light technical	
Flickering	1
Stroboscopic effect	1.6

Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
Inrush current	2.9 A
Inrush time	0.103 ms
Power Factor (Min)	0.9

Controls and dimming	
Dimmable	No

Ledinaire Waterproof

Mechanical and housing	
Housing Material	Polycarbonate
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Stainless steel
Optical cover/lens finish	Opal
Overall length	1258 mm
Overall width	69 mm
Overall height	59 mm
Color	Gray and white
Dimensions (Height x Width x Depth)	59 x 69 x 1258 mm (2.3 x 2.7 x 49.5 in)

Approval and application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]

Initial performance (IEC compliant)	
Initial luminous flux (system flux)	2500 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	120 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	<5
Initial input power	20 W
Power consumption tolerance	+/-10%

Over time performance (IEC compliant)	
Control gear failure rate at median useful life 50000 h	7.5 %
Lumen maintenance at median useful life* 50000 h	L70


Application conditions	
Ambient temperature range	-20 to +45 °C
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Yes

Product data	
Full product code	871016336292299
Order product name	WT060C LED25S/840 PSU TW1 L1200
EAN/UPC - Product	8710163362922
Order code	36292299
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401892880
Net Weight (Piece)	0.800 kg



Dimensional drawing

WT060C TW



L1200	69	69	59	1258	220 - 260	220 - 260
L1500	69	69	59	1508	160 - 200	160 - 200

WT060C LED25S/840 PSU TW1 L1200

© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.