

Serial PCI Express Card

One Port, x1 Lane

Part No.: 153492

EAN-13: 0766623153492 | UPC: 766623153492

This Serial PCI Express Card balances cost, performance, compatibility and advanced features for computing platforms

The Manhattan Serial PCI Express Card quickly and easily adds one DB9 port to PCI Express-enabled desktop systems to connect and communicate with serial peripheral devices. It can be configured to achieve baud rates up to 230,400 bps to take advantage of maximum PCI Express bus speeds. Compliance with PCI Express 1.1 specifications ensures that most PCI Express Card-equipped desktop computers and devices can operate at peak performance. It fits PCI Express x1, x2, x4, x8 and x16 lane buses, and configurable COM port settings provide a flexible way to customize its use to various needs.

Features:

- Easily adds one configurable serial RS232 (DB9) port to a desktop computer
- Fits PCI Express x1, x2, x4, x8 and x16 lane buses
- Serial data transfer rate up to 2 Mbps
- Fits standard and low-profile PCI slots
- Compatible with industry standards 16C550/16C552/16C554/16C750 UART
- Plug and Play; Windows and Linux compatible
- Three-year warranty

Specifications:

Standards and Certifications
• PCI Express 1.1
• PCI Power Management 1.2
• CE
• FCC
• RoHS

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

• WEEE

Port Specifications
• DB9 male port
• Programmable baud rate up to 230,400 bps
• WCH382L chipset
• Single 3.3 V operation
• 256-byte transmit/receive FIFO
• Compatible with 16C550/16C552/16C554/16C750 UART

Bus Specifications
• PCI Express x1
• Bus speed: 2.5 Gbps
• Compliant with PCI Express 1.1 specifications
• Compliant with PCI Power Management 1.2 specifications

Physical
• Dimensions (with regular bracket): 120 x 68 x 20 mm (4.7 x 2.6 x 0.8 in.)
• Weight (with regular bracket): 42.5 g (1.5 oz.)

System Requirements
• Windows NT4.0/2000/XP/Server 2003/Vista/7/8/10 or Linux
• PCI Express-enabled system with an available PCI Express slot

Package Contents
• Serial PCI Express Card
• Standard and low-profile brackets
• Instructions





For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.









For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.