

MASTER LED candles and lusters

MASTER LEDcandle DT 5.5-40W E14 B38 CL UK

Delivering incandescent-like sparkling light effects, MASTER LED candles and lusters are ideal for general and decorative lighting in the hospitality industry as well as in home environments. Mounted in full view in chandeliers, wall scones or modern luminaires, the clear or frosted glass candles and lusters fit all existing fixtures with an E14, B15, B22 or E27 socket, and enhance the aesthetic appeal of the chandelier or luminaire both when on and off, with their unique, eye-catching lens design. They produce a beautiful sparkling warm light that delivers huge energy savings and minimizes maintenance cost.

Product data

General Information	
Cap-Base	E14 [E14]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	25000 h
Switching Cycle	50000X

Light Technical	
Color Code	822-827 [tunable warm white]
Luminous Flux (Nom)	470 lm
Color Designation	Warm Glow(WG)
Correlated Color Temperature (Nom)	2200 2700 K
Luminous Efficacy (rated) (Nom)	85.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Nom)	5.5 W
Lamp Current (Nom)	26 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.9
Voltage (Nom)	220-240 V

Temperature	
T-Case Maximum (Nom)	80 °C

Controls and Dimming	
Dimmable	Yes

MASTER LED candles and lusters

Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	B38

Approval and Application	
Energy Consumption kWh/1000 h	6 kWh

Product Data	
Full product code	871951430614101
Order product name	MASTER LEDcandle DT 5.5-40W E14 B38 CL UK

EAN/UPC - Product	8719514306141
Order code	929002491099
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002491099
Net Weight (Piece)	0.053 kg

Dimensional drawing



B38 220-240V 5.5-40W 470lm 27-22K E14

Product	D	C
MASTER LEDcandle DT 5.5-40W E14 B38 CL UK	38 mm	113 mm

Photometric data



LEDcandle MAS SLR1 5,5W B38 E14 827 CL-GUL



LEDcandle MAS SLR1 B38 5,5W E14 827 CL-LDD

MASTER LED candles and lusters

Photometric data



LEDcandle MAS SLR1 5,5W B38 B15 827 CL-POC

Lifetime



LEDspots LED 25K



LEDspots LMP 25K

© 2021 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.