MPN: 0070-04362IR

Mercury SX 362IR Dome camera



2.7-12mm Lens 1080P@60fps UWDR Vandal Proof IK10, Auto Focus Motorised P Iris-Lens, IR 45M, Heater POE, 24VAC
Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Form factor: Dome, Product colour: White, International Protection (IP) code: IP66, IK10. Field of view (FOV) angle: 199° (Wide) ; 31° (Tele). Sensor type: CMOS, Optical sensor size: 1/3" Progressive CMOS. Fixed focal length: 2.7 - 12mm

- 1080p@ 60fps (2MP)
- Ultra Wide Dynamic Range 120dB
- Motorised 2.7-12mm P-Iris Lens
- Real Time in all Resolutions
- Multi Codec Support (H.264/H.265)
- IP67, IK10
- ONVIF Profile S/ G/ Q/ T support
- POE (IEEE 802.3af)
- HDR Engine Gen3
- 4 year Warranty

Specifications

Audio	**Audio formats supported**	G.711, G.726, AAC, LPCM
	Built-in speaker(s)	No
Camera	**Adjustment shutter speed**	Auto/Manual
	Camera pan control	No
	Camera shutter speed	1~1/10.000 s
Design	**Form factor**	Dome
	Housing material	Aluminium
	IK code	IK10
	Mounting type	Ceiling/Wall/Pole
	Product colour	White
	Weatherproof	Yes
Features	**NDAA Compliance**	Yes
Image sensor	**Number of effective pixels (H x V)**	1920 (H) x 1080(V) pixels
	Progressive scan	Yes
Legal Information	**Country of Origin**	Taiwan
	Tariff No.	8525890000
	UNSPSC Code	46171610
Lens system	**Auto focus**	Yes
	Focal length range	2.7-12 mm
	Number of lenses	1
Management features	**Firmware upgradeable**	Yes

Management features	**Reset button**	Yes
	Web-based management	Yes
Network	**Ethernet LAN**	Yes
	Networking standards	IEEE 802.1X
	Wi-Fi	No
Night vision	**B/W night vision distance**	45 m
	Night vision	Yes
	Night vision distance	45 m
Operational conditions	**Operating temperature (T-T)**	-30-55 °C
	Storage relative humidity (H-H)	10-90 %
Other features	**Audio output**	Yes
	IR control	Auto, Manual
Package dimensions	**Depth (package,cm)**	17.5 cm
	Gross Weight (Package, kg)	1.1 kg
	Height (package,cm)	17.4 cm
	Width (package,cm)	18 cm
Packaging content	**AC adapter included**	No
	Sun shield included	No
Performance	**Alarm input/output**	Yes
	Connectivity technology	Wired
	Infrared (IR) cut-off filter	Yes
	Placement supported	Indoor & outdoor
	Remote viewing	Yes
	Thermal module	No
	Type	IP security camera
Power	**Power consumption (Power over Ethernet (PoE))**	12.95 W
	Power over Ethernet (PoE)	Yes
Product dimensions	**Net Weight (Product, kg)**	1 kg
	Product Depth	14 cm
	Product Height	14 cm
	Product Width	14 cm
Security	**Alert notification type**	E-mail
	HTTPS encryption	Yes
	Temperature sensor	No
	Video motion detection	Yes
Technical details	**Audio input**	Yes
	Lens type	Varifocal
	Number of video streams	4

Technical details	**Power source**	POE or 12V DC
	Removable IR-cut filter	Yes
	Suitable for outdoor use	Yes
Vendor information	**Brand Name**	Ernitec
	Homepage	http://www.ernitec.com
	Warranty	5 Year(s)
Video	**3D NR (Noise Reduction)**	Yes
	Analog signal format system	Not supported
	Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
	Flip & mirror	Yes
	Frame rate	50 fps
	Privacy masking	Yes
	Text caption overlay	Yes
	Time stamp overlay	Yes
	Total megapixels	2 MP
	Video compression formats	H.264, H.265, M-JPEG
	Video streaming	Yes