

ITP-80II WF

Model	**ITP-80 II WF**	Colour	Black
Printing method	Direct thermal	Printing speed	260mm/sec
Printing width	79.5±0.5mm	Paper diameter	80mm
Paper thickness	0.06˜0.08mm	Print columms	576 dots/line 512 dots/line
Line space	3.75mm (changeale using commmads)	Input buffer	2045 Kbytes
Character size	ANK, FontA: 12x24 dots FontB: 9x17 dots simplified/tradicional Chinese: 24x24 dots	Bar code	UPC-A/UPC-E/JAN13 (EAN13)/JAN8 (EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128/QR CODE/PDF417
NV flash	256 Kbytes	Input buffer	2048 Kbytes
Power spply	DC 24 V=2.5 A	Cash drawer	DC 24 = 1 A
Interface	USB+Wifi	Auto cutter	Partial
Reliability	Printing head life: 100 km Auto cutter life: 1.000.000 cuts	Working environment	Temperature (0˜45ºc), humidity (10˜80%)
Storage environment	Working temperatura: 0-45ºC Humidity: 10-80%	Drivers	Win9X/WinME/Win200x/WinNT/ WinXP/WinVista/Win7/Win8/Win10 /Linux/POS
Command	Compatible with ESC/POS	Gross weight	1,70 Kg
Dimension	190x145x150 mm (DxWxH)	Warranty	2 years