PREMIER

ILP-500



Model	ILP-500
Printing Features	
Resolution	203 DPI
Printing method	Thermal Transfer / Direct Thermal
Max.print speed	127 mm (5”)
Max.print width	108 mm (4.25”)
Max.print length	1778mm (70")
Media	
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	25.4-115 mm (1.0”-4.6”)
Media thickness	0.06~0.18 mm
Media core diameter	25.4 ~ 50.8 mm (1" ~ 2")
Ribbon length	Max. 90m
Ribbon width	25.4mm-110mm (1"-4.3")
Label length	10 mm ~1778 mm
Label roll capacity	127 mm (5“) (External diameter) OD (outer diameter)
Ribbon core inner diameter	12.7 mm (0.5")
Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory / Flash memory can be expanded to Max. 4 GB
Interface	USB / Ethernet
Sensors	①Gap sensor ②Cover opening sensor ③Black mark sensor ④Ribbon sensor
Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
2D barcode	PDF-417, Maxicode, DataMatrix, QR code
Rotation	0°, 90°, 180°, 270°
Emulaion	TSPL, EPL, ZPL, DPL
Physical Features	
Dimension	246mm*199mm*168mm (D*W*H)
Weight	1.62 Kg
Reliability	
Print head life	30 km
Software	
Driver	Windows/Linux/Mac
SDK	WindowsAndroid/iOS
Power supply	
Power supply	Input ： AC 100-240V Output ： DC 24V, 2.5A
Environmental Conditions	
Operation environoment	5 ~ 40°C (41~104°F), Humidity: 25 ~ 85% non-condensing
Storage environment	-40 ~ 60°C (-40~140°F), Humidity: 10 ~ 90% non-condensing
Warranty	
Warranty	2 years

MUZYBAR COMPUTER, S.L.
Avda. Cardenal Benlloch, 48 Bajo. 46021 Valencia. T. 960 910 334 info@muzybar.es www.muzybar.es