PHILIPS

Lighting



Ledinaire SlimDownlight

DN065B G3 LDNR LED10/840 10.5W L150 SQ

The LEDINAIRE range contains a selection of popular off-the-shelf LED luminaires that come with the high Philips quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need

Product data

General information	
Light source color	840 neutral white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Beam angle 110°
Luminaire light beam spread	110°
Connection	Screw connection block 2-pole
Cable	Cable 0.2 m without plug
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	280
EU RoHS compliant	Yes

Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Inrush current	5.05 A
Power Factor (Min)	0.9

Controls and dimming	
Dimmable	No

Mechanical and housing	
Housing Material	Metal
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Optical cover/lens finish	Matte
Overall length	175 mm
Overall width	175 mm
Overall height	39 mm
Color	White

Ledinaire SlimDownlight

Dimensions (Height x Width x Depth)	39 x 175 x 175 mm (1.5 x 6.9 x 6.9 in)

Approval and application	
Ingress protection code	IP20(front IP40)
Mech. impact protection code	IK03 [0.3 J]

Initial performance (IEC compliant)	
Initial luminous flux (system flux)	1000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	90.00 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	80
Initial chromaticity	(IEC4000K, 0.38, 0.38) 5SDCM
Initial input power	11 W
Power consumption tolerance	+/-10%


Over time performance (IEC compliant)	
Median useful life L70B50	25000 h
Lumen maintenance at median useful life* 50000 h	L65

Application conditions	
Ambient temperature range	-20 to +40 °C
Suitable for random switching	No

Product data	
Full product code	871951432900300
Order product name	DN065B G3 LDNR LED10/840 10.5W L150 SQ
EAN/UPC - Product	8719514329003
Order code	32900300
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	929002664332
Net Weight (Piece)	0.330 kg




Dimensional drawing




Cut-out hole diameter - L150mm

DN065B G3 LDNR LED10/840 10.5W L150 SQ

Photometric data



Donwlight DN065B G3 LDNR 840 L150 SQ-GUL



Donwlight DN065B G3 LDNR 840 L150 SQ-LDD



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.